

TOPEC[®]

TOPEC is an aluminum modular formwork slab system without beams.



At Work For You

TOPEC® modular slab formwork from Hünnebeck makes the shuttering and stripping of slabs much faster and demonstrably more economical than conventional slab formwork systems. This is because the TOPEC system has just two basic parts – panels and props, with a drophead as an optional extra. You'll get perfect results in just a few working steps.

► Product advantages TOPEC®

Easy handling

Robust yet lightweight aluminum design provides ergonomic and fatigue-free handling
Columns and other obstacles are easy to work around with TOPEC's adjustment solutions

Safe

Can easily be used with PROTECTO edge guard
Safe forming and stripping up to a height of 3.50 m from the ground in three easy working steps

Economical

Giant panel 180 x 180 cm covers a forming area of 3.24 m²

Versatile

Versatile due to various adjustment parts and alternatives
TOPEC can be used in combination with TOPMAX floor tables and serves as an ideal and speedy fill-in solution for adjustment areas
Adjustment panels can continuously extend in widths from 55 to 90 cm with no extra props required




► Columns and other obstacles are easy to work around with TOPEC's adjustment solutions

Technical specifications TOPEC®

Product description	Modular slab formwork
Panel widths	45 60 75 90 180 cm
Panel lengths	90 180 cm
Adjustment panel	55 – 90 x 90 cm 55 – 90 x 180 cm
Profile thickness	14 cm aluminum frame profile
Form lining types	ECOPLY® full plastic composite sheet Plywood (340 g/m ²)
Form lining thickness	11 mm ECOPLY full plastic composite sheet 10 mm plywood
Weight per panel	Panel 180 x 90 cm = 22.20 kg Panel 180 x 180 cm = 47.10 kg
Relevant standards	Complies with DIN 18202
Maximum slab thickness	75 cm (with 60 cm wide panels)
Corrosion protection	Powder-coating
Standard shoring	EUROPLUS ^{new} props 20 kN 30 kN
Special shoring	MODEX scaffolding
Bearings	TOPEC bearing Edge support N Drophead
Assembly/stripping times	$t = 0.20 - 0.40 \text{ h/m}^2 *$
Special features	<ul style="list-style-type: none"> • Adjustment panels (fully telescopic) • ECOPLY® full plastic composite sheet • Alternatively with TOPEC drophead for early striking • EUROPLUS^{new} with quick-lowering mechanism • TOPEC lift hydraulically positions the panels exact and flush



 Safe forming and stripping up to a height of 3.5 m from the ground in three easy working steps. Just hook on – push up – prop it.

* Time calculation (average) by Hünnebeck



► This giant panel 180 x 180 cm has a forming area of 3.24 m².



► TOPEC's lightweight aluminum design ensures ergonomic and fatigue-free operations



► Can easily be used with PROTECTO edge guard

TOPEC® integrates with

- TOPMAX®
- MODEX® shoring
- EUROPLUS® new
- PROTECTO®



If you want to learn more, watch our video.

UAE
Phone: +971 4 8132000
Egypt
Phone: +202 2359 1568

Saudi Arabia
Phone: +966 12 691 7690
Malaysia
Phone: +60 3 42965455

Singapore
Phone: +65 68 626122

